













CONTENTS

INTRODUCTION	2
01 PENCIL GRINDER	3
Icon Library	4
Oil Free Pencil Grinder - SPT line	5
Pencil Grinder - SPM line	6
Small Angle Sander - RPM25R	7
Oil Free Turbine Pencil Grinder - ST100	8



INTRODUCTION



WHY SELECT

With over 50 years experience, ATA is a global leader in the provision of high-end industrial air tools. Our comprehensive portfolio offers a solution for every grinding and finishing application, optimizing processes in terms of economic efficiency, reliability and safety. Our customers come from a wide variety of industries, including automotive, aerospace, foundries, metal fabrication, oil & gas, marine, medical, rail and power & energy.

DEDICATED TO QUALITY

Quality and continuous improvement are priorities at ATA. We strive for exemplary quality in our products and services. In the procurement of goods and services, we look for partnerships with suppliers that apply the same principles of quality assurance. Our Quality Management System is certified to ISO 9001:2015.

INNOVATION FROM DAY ONE

Founded in 1963, ATA is a true pioneer in industrial air tools. Since then we have continued to provide our customers with products and solutions to suit their processes and requirements. Our industrial expertise and detailed application know-how have led to pioneering developments.







INTERNATIONAL OFFICES

ATA Tools Ltd., IDA Business & Technology Park, Killygarry, Cavan, Co. Cavan, H12 DK46, Ireland

> T: +353 (0) 49 432 6178 F: +353 (0) 49 432 6298 E: sales@atagroup.ie

W: www.atagroup.co

UK OFFICES

ATA Garryson Ltd., Spring Road, Ibstock, Leicestershire, LE67 6LR, United Kingdom


T: +44 (0) 1530 261 145 F: +44 (0) 1530 262 801 E: sales@atagarryson.com W: www.atagroup.co

US OFFICES

ATA Tools, Inc. 7 Ascot Parkway, Cuyahoga Falls, Ohio 44223, USA

> T: +1 330 928 7744 F: +1 330 849 2977 E: sales@atatools.com W: www.atagroup.co





ICON LIBRARY



Legacy Line - Long-standing industry standard air tools



FEATURES & SAFETY



Low Vibration



Wear Protective Goggles



Wear Protective Mask



Wear Ear Protection



Oil Required



Oil Free

MODEL SPECIFICATIONS



Speed (rpm)



Power (hp)



Power (watt)



Weight (kg)



Weight (lb)



Length



Height (mm)



Consumption (m3/min)



Air Consumption (cfm)



Noise Level (db.(A))



Standard Collet Size (mm)



Collet Options (mm)



Collet Type



Exhaust Type



Lever Type



Spindle Thread



Auto-balancer



Side Handle Type

CONSUMABLES



Tungsten Carbide Burs



Tungsten Carbide Burs (Solid)



Mounted Points



Flexidisc®



Mini-Flexidisc ™



Flap Discs



Jumbo Flap Discs



Minidiscs



Quickchange Discs



Fibre Discs



Belts



Flapwheels



Wire Cup Brushes



PENCIL GRINDER - Oil Free Pencil Grinder - SPT Line















FEATURES & BENEFITS

- Air propulsion motor no lubrication required
- Slim turbine design for operator comfort
- Ceramic bearings offer extended spindle life and smooth operation
- Simplicity of motor design no wear on components in motor
- Light weight for operator comfort

	Model		SPT100R	SPT80R	
	Speed (rpm)		100,000	80,000	
	Power (hp)		0.08	0.08	
9	Power (watt)		63	63	
	Weight (kg)		0.15	0.15	
	Weight (lb)		0.33	0.33	
	Length (mm)		135.00	135.00	
(Ī)	Height (mm)		22.00	22.00	
	Air Consumption (m3/min)		0.17	0.17	
	Air Consumption (cfm)		6.00	6.00	
9	Noise Level (db.(A))		70	68	
	Standard Collet Size (mm)	\geq	3	3	
	Collet Options (mm)		2.34	2.34	
	Collet Type	>	СС Туре	CC Type	
	Exhaust Type		Rear	Rear	
	Lever Type	>	Roll	Roll	

Recommended Consumables (Catalogues available upon request)



Tungsten Carbide Burs

(3mm) Solid

• Always ensure that the speed of the air tool never exceeds the maximum operating speed of the consumable.





Ordering Information

International T: +353 (0) 49 432 6178 **E:** sales@atagroup.ie **UK T:** +44 (0) 1530 261 145 **E:** sales@atagarryson.com **US T:** +1 330 928 7744 **E:** sales@atatools.com

PENCIL GRINDER - Pencil Grinder - SPM Line















FEATURES & BENEFITS

- Slim body design for intricate work
- High speed results in a finer finish
- Small diameter facilitates precise control
- Improved roll throttle offers enhanced torque
- Moulded body for operator comfort
- Removable collet guard

	Model	SPM80R	SPM60R	SPM45R
	Speed (rpm)	80,000	60,000	45,000
	Power (hp)	0.10	0.11	0.11
	Power (watt)	80	85	85
	Weight (kg)	0.17	0.17	0.17
	Weight (lb)	0.38	0.38	0.38
∌	Length (mm)	135.00	135.00	135.00
D	Height (mm)	22.00	22.00	22.00
3	Air Consumption (m3/min)	0.20	0.23	0.23
	Air Consumption (cfm)	7.00	8.00	8.00
9	Noise Level (db.(A))	66	68	68
ightharpoons	Standard Collet Size (mm)	3	3	3
ightharpoonup	Collet Options (mm)	2.34	2.34	2.34
	Collet Type	CC Type	ССТуре	СС Туре
	Exhaust Type	Rear	Rear	Rear
	Lever Type	Roll	Roll	Roll

Recommended Consumables (Catalogues available upon request)



Tungsten Carbide Burs (3mm)



Mounted Points (3mm)

• Always ensure that the speed of the air tool never exceeds the maximum operating speed of the consumable.








International T: +353 (0) 49 432 6178 **E:** sales@atagroup.ie **UK T:** +44 (0) 1530 261 145 **E:** sales@atagarryson.com **US T:** +1 330 928 7744 **E:** sales@atatools.com

PENCIL GRINDER - Small Angle Sander - RPM25R







FEATURES & BENEFITS









- Slim body right angled sander designed for precision deburring and sanding
- Suitable for 20mm, 25mm and 38mm ATA Discs
- Small angle head to facilitate access to restricted areas
- CD type collet accommodates 3mm (1/8") shank burs or mounted

	Model	RPM25R	
	Speed (rpm)	25,000	
	Power (hp)	0.11	
(7)	Power (watt)	85	
	Weight (kg)	0.23	
	Weight (lb)	0.51	
	Length (mm)	141.00	
(1)	Height (mm)	33.50	
	Air Consumption (m3/min)	0.23	
	Air Consumption (cfm)	8.00	
9	Noise Level (db.(A))	69	
	Standard Collet Size (mm)	3	
	Collet Options (mm)	2.34	
	Collet Type	CD Type	
	Exhaust Type	Rear	
	Lever Type	Roll	

Recommended Consumables (Catalogues available upon request)



Tungsten Carbide Burs (3mm)



Mounted Points (3mm)



Quickchange Disc (20mm, 25mm & 38mm)

• Always ensure that the speed of the air tool never exceeds the maximum operating speed of the consumable.



Ordering Information

International T: +353 (0) 49 432 6178 E: sales@atagroup.ie **UK T:** +44 (0) 1530 261 145 **E:** sales@atagarryson.com **US T:** +1 330 928 7744 **E:** sales@atatools.com

PENCIL GRINDER - Oil Free Turbine Pencil Grinder - ST100

















- Oil free operation no contamination of workpiece
- High speed results in a fine finish
- Small diameter facilitates precise control
- Ergo sleeve fitted for operator comfort

	Model		ST100
	Speed (rpm)		100,000
	Power (hp)		0.06
9	Power (watt)	\geq	40
	Weight (kg)		0.24
	Weight (lb)		0.53
	Length (mm)		150.00
1	Height (mm)		27.00
(a)	Air Consumption (m3/min)		0.17
③	Air Consumption (cfm)		6.00
9	Noise Level (db.(A))		62
	Standard Collet Size (mm)		3
	Collet Options (mm)		2.34
	Collet Type		CC Type
	Exhaust Type		Front
Θ	Lever Type		Roll

Recommended Consumables (Catalogues available upon request)





Tungsten Carbide Burs (3mm) Solid

(3mm)

• Always ensure that the speed of the air tool never exceeds the maximum operating speed of the consumable.



UK T: +44 (0) 1530 261 145 **E:** sales@atagarryson.com **US T:** +1 330 928 7744 **E:** sales@atatools.com



Notes



Ordering Information

